Machine Specifications

	Item			PUMA 280	PUMA 280L	PUMA 280M	PUMA 280LM
Capacity	Swing over bed		mm	630			
	Swing over saddle		mm	500			
	Recom. turning diameter		mm	255			
	Max. turning diameter		mm	420		410	
	Max. turning length		mm	658	1,078	610	1,030
	Bar working diameter		mm	76			
Main spindle	Spindle speed		rpm	3,500			
	Spindle nose		ASA	A2 #8			
	Spindle bearing diameter (Front)		mm	136			
	Spindle bore diameter		mm	86			
	Cs spindle index angle		deg	-		360(0.001°)	
Carriage	Travel distance	X-axis	mm	242(32+210)		242(37+205)	
		Z-axis	mm	680	1,100	680	1,100
	Rapid traverse	X-axis	m/min	20			
		Z-axis	m/min	24			
Turret	No. of tool station		st	10		12st(BMT55P)	
	OD tool height		mm	25 × 25			
	Boring bar diameter		mm	ø50		ø40	
	Indexing time (1st swivel)		sec	0.15			
	Rotary tool spindle speed		rpm	-		5,000	
Tail stock	Quill diameter		mm	100			
	Quill bore taper		MT#	MT#5			
	Quill travel		mm	100			
Motors	Main spindle motor (30 min)		kW	22			
	Servo motor	X-axis	kW	3.0			
		Z-axis	kW	4.0			
	Rotary tool spindle motor		kW	-		5.5	
	Coolant pump		kW	0.4			
Power source	Electric power supply(Rated capacity)		kVA	36.52		37.91	
Machine size	Machine height		mm	1,735			
	Machine dimension	length	mm	3,418	3,838	3,418	3,838
		width	mm	1,670			
	Machine weight		kg	4,700	5,300	4,900	5,500

※ { } : Optional

Standard Feature

- Coolant supply equipment
- Foot switch
- Front door Safety Lock
- Full enclosure chip and coolant shield
- Hand tool kit (including small tool for operations)
- Hydraulic chuck and actuating cylinder
- Hydraulic power unit
- Levelling jack screw & plates
- Live tail center
- Lubrication equipment
- Manual Tail Stock
- Manuals
- Safety precaution name plates
- Soft jaws (total)
- Standard tooling kit (tool holder & boring sleeve)
- Work light

Optional Feature

- Air blast for chuck jaw cleaning
- Automatic door
- Automatic door with safety device
- Bar feeder interface
- Built-in center (MT#4)
- Chip conveyor
- Coolant temperature control unit (Heater & Chiller)
- Dual chucking pressure
- Electric power transformer
- Hardened & ground jaws
- Hyd. Chuck
- Hyd. steady rest
- Parts catcher (on M type)
- Pressure switch for chucking pressure check
- Proximity switches for chuck clamp detection
- Proximity switches for quill position detection
- Signal tower (Red, Yellow, Green)
- Special chucks
- Tool monitoring system

NC Specifications

	Item	Spec.	Fanuc-0iTC	Fanuc 21-iTB
Controls	Controlled axes		X,Z,C(!)	X,Z,C(!)
	Simultaneously controlled axes	Std. 2 axes	3 axes(!)	3 axes(!)
Axis functions	Backlash compensation	0~±9999 pulses	O	O
	Cs contouring control		O(!)	O(!)
	Follow-up / Chamfering on/off		O	O
	HRV control		O	O
	Increment system 1/10	0.0001mm / 0.00001"	O	O
	Least input increment	0.001mm / 0.0001"	O	O
	Stored stroke check1	Overtravel control	O	O
Operation	Automatic operation(memory) / Buffer register		O	O
	Search function	Sequence NO. / Program NO.	O	O
	Manual handle feed	X1, X10, X100	O	O
Interpolation	1st, 2nd reference position check / return	G27/G28, -/ G30	O	O
	Circular interpolation	G02, G03	O	O
	Continuous thread cutting		O	O
	Dwell	G04	O	O
	Linear interpolation	G01	O	O
	Multiple threading /Thread cutting retract		O	O
	Polar coordinate interpolation	G12.1, G13.1	O(!)	O(!)
	Thread cutting / Synchronous cutting		O	O
Feed functions	Feed per minute / Feed per revolution	G98 / G99	O	O
	Feedrate override	0 - 200 %(10% unit)	O	O
	Jog feed override	0 - 2,000 mm/min	O	O
	Rapid traverse override	F0/ 25 / 100 %	O	O
	Tangential speed constant control		O	O
Axuiliary & Spindle functions	1st Spindle orientation		O	O
	3rd spindle serial output		-	-
	Constantant surface speed control	G96, G97	O	O
	M-function	M3 digit	O	O
	Multi-spindle control		O(!)	O(!)
	Rigid tapping		O	O
	Spindle speed override	0~150%	O	O
	Spindle synchronous control		-	-
	Sub spindle orientation		-	-
Programming functions	Absolute / Incremental programming		O	O
	Canned cycle for drilling	G80 series	O	O
	Custom macro B		O	O
	Decimal point programming/pocket calculator type decimal point programming		O	O
	Direct drawing dimension programming		O	O
	eZ Guide i	Conversational programming	Opt.	O
	Maximum program dimension	±99999.999mm/(±9999.9999 inch)	O	O
	Multi repetitive canned cycle	G70~G76	O(!)	O
	Multi repetitive canned cycle 2		O	O
	Optional block skip(without hardware)	Total 9(Only NC function)	O	O
	Program number / Sequence number	O4 digits / N5 digits	O	O
	Programmable data input	G10	O	O
	Sub program call	Nested holds4	4	4
	Tape format for FANUC series 10/11		O	O
	Tape format for FANUC series 15		-	-
	Work coordinate system selection	G52, G53, G54~G59	O	O
Tool functions	Auto tool offset		O	O
	Tool monitoring system		-	Opt.
	Direct input of tool offset value measured B		O	O
	Tool geometry / wear compensation	Geometry & wear data	O	O
	Tool life management		Opt.	Opt.
	Tool nose radius compensation	G40~G42	O	O
	Tool number command(T-code function)	T2+2 digits	O	O
	Tool offset pairs		64	64
	Tool offset value counter input		-	O
Editing op. functions	Background editting		O	O
	Expanded part program editting	Copy, Move, Change of NC program	O	O
	No. of Registered programs		400EA	200EA
	Part program editing / Program protect		O	O
	Part program storage length *1		640m	640m
Setting & display	Display of spindle speed and T-code at all screen		O	O
	Help function	Alarm&Operation display	O	O
	Self diagnostic function		O	O
	Servo setting screen / Spindle setting screen		O	O
	Tool path graphic display		O(!)	Opt.(!)
Data input & output	I/O interface	RS-232C	O	O
	Memory card input and output		O	O
	Reader puncher control	CH1 interface	O	O
Other functions	Ethernet function	Embedded ethernet function	Opt.	O
	MDI / DISPLAY unit		8.4" Color LCD	10.4" color LCD
	PMC system		O	O

* 1 : Standard Part program length is different on export condition. On the addition of optional functions, its length can be reduced.

O:Std OPT:Option (!):only M type

External Dimension

unit : mm

PUMA 280 /280 M

TOP VIEW



FRONT VIEW



SIDE VIEW



External Dimension

unit : mm

PUMA 280 L /280 LM

TOP VIEW



FRONT VIEW



SIDE VIEW



Tooling System

unit : mm

PUMA 280/280L



PUMA 280LM



Tool Interference Diagram

unit : mm

PUMA 280/280L

12 stations turret



10 stations turret(Opt.)



PUMA 280LM

12 stations turret



Working Ranges

unit : mm

PUMA 280/280L

OD tool holder



ID tool holder



Extended OD Tool Holder



Face Tool Holder



( ) : Long Bed

Working Ranges

unit : mm

PUMA 280M/280LM

OD tool holder



ID tool holder



Straight milling Unit



Angular milling Unit



( ) : Long Bed

Machine Capacity



* Actual results may differ depending on cutting conditions.

Heavy-Duty Cutting

Chip removal rate
530 cm³/min

Cutting depth
7.62 mm/side

Carbon Steel, SM45C

Cutting speed
183 m/min

Feedrate
101.6 m/rev

Working Range

A : Max. turning dia.
420/410* mm

B : Max. turning length
658/610* [1,078/1,030*] mm

C : Max. bar working dia.
76 mm



* on M type machine, [ ] : long bed machine

Slideway Width

X-axis : 254 mm

Z-axis : 300 mm



Additional Equipment



Heavy-Duty Cutting

Widely spaced guide ways and a heavy duty tail stock body ensure ample rigidity. The tailstock body can be positioned with traction bar that engages with the carriage. The traction bar movement and body clamping are programmable.

Tailstock specification		
Tailstock travel	mm	680 [1,100]
Tailstock quill diameter	mm	100
Taper hole of tailstock quill		MT#5 <Live center>
Tailstock quill travel	mm	100

[ ] : Long bed machine

Collet chuck


Part catcher

Tool pre-setter (Standard)

Signal tower


Oil skimmer (Standard)

Chip conveyor

Chuck air(or coolant) blower


Work measurement


Part conveyor

Main Spindle

■ Power-Torque Diagram Main Spindle

- Spindle speed range : 3,500 RPM
- Motor power : 30 Hp



Max. spindle speed **Motor (30min)**

3,500 rpm **22 kW**

Main Spindle

Both main and sub spindle have characteristic as integral motor spindles that are whole covered with each oil cooling system to ensure remarkable range of applications from heavy duty cutting with high power at low speed to fine to finish cutting at high speed and optimize thermal displacement.



Headstock and Spindle

The powerful spindle motor enables heavy stock removal, reducing the number of roughing passes required.

Cross Section of Main Spindle



Turret



Index time (1-station swivel)

0.15 sec.

No. of tool station

10 stations

The heavy duty design provides unsurpassed rigidity for heavy stock removal, fine surface finishes, long boring bar overhang ratios, and extended tool life. Turret indexing is direct and bi-directional, with a 0.15 second next station index time. Turning tools are securely attached to the turret by wedge clamps.

Rotary Tool Turret*



No. of tool station

12 stations

12 tool stations turret(BMT55P) make it possible to complete complicated parts requiring many tools in just one set-up. Reliable servo driven turrets reduce the total cycle time required to machine parts.

• Preci-flex adapter application

• Collet application

Radial BMT Turret



BMT turret is 12 stations,
thus providing the ability to use up to 24 tools.

■ Rotary tool spindle power-torque diagram

- Spindle speed range : 5,000 rpm



High Performance and Heavy Duty Turning Center

Combining rigid slant bed construction with advanced technology for superior machining of mid to large sized workpieces.

PUMA 280

DOOSAN

Doosan Infracore
Machine Tools

PUMA 280

High Productivity Turning Center